

B17

**PHOTOSENSITIVE COMPOSITION**

**Patent number:** JP6289612  
**Publication date:** 1994-10-18  
**Inventor:** YONEYAMA NOBUAKI; TANAKA KIMIAKI  
**Applicant:** NIPPON ZEON CO  
**Classification:**  
- international: C08G8/08; C08G8/00; C08G85/00; G03F7/004;  
G03F7/022; G03F7/038; G03F7/039; C08G8/08;  
C08G8/00; C08G85/00; G03F7/004; G03F7/022;  
G03F7/038; G03F7/039; C08G8/00; (IPC1-7):  
G03F7/038; C08G8/08; C08G85/00; G03F7/004;  
G03F7/039  
- european:  
**Application number:** JP19930097160 19930331  
**Priority number(s):** JP19930097160 19930331

[Report a data error here](#)**Abstract of JP6289612**

**PURPOSE:**To obtain a photosensitive compsn. excellent in storage stability and having coating property by bringing a liquid photosensitive compsn. or a soln. of the resin component which constitutes the photosensitive compsn. into contact with an ion exchange resin and performing ion exchange treatment. **CONSTITUTION:**A liquid photosensitive compsn. or a soln. of the resin component which constitutes the photosensitive compsn. is brought into contact with an ion exchange resin for ion exchange treatment. The object photosensitive compsn. includes compds. generally called as a resist. As for the ion exchange resin, two kinds of resins, an anion exchange resin and a cation exchange resin, are usually used, and in this method, a cation exchange resin is mainly used to remove metal ions. The ion exchange resin is classified as a macroporous type, gel type, etc., according to kinds of base bodies, and any type of resin can be used. Further, both of a nonwater-base or a water-base resin can be used. The cation exchange resin to be used is a H<+> type as used in a conventional method.

.....  
Data supplied from the esp@cenet database - Worldwide